

STX 5000T

Self-service terminal with touch screen



Cover for protecting touch screen

Industrial touch screen with very high brightness allowing convenient use of the terminal even in bright sunlight

Stainless steel housing

Barcode reader

Industrial printer for printing weighing tickets



Self-service terminal STX 5000T

TECHNICAL SPECIFICATIONS

CATEGORY	PARAMETER
TECHNICAL DESCRIPTION	
Panel size	15"
Active display area (mm)	304.1 (H) x 228.1 (V)
Resolution	1028 x 768
Brightness	1000 (typical)
Contrast ratio	700:1 (typical)
Viewing angle	-80~80 (H); -70~70 (V)
Number of colors	16.2 (6 bits/color)
Optional touch screen	Projected capacitive multi-touch
POWER INFORMATION	
Power source	12 V DC in, with external AC-DC adapter (100~240V)
Power consumption	25 W typical, normal operation
OPERATING ENVIRONMENT	
Storage temperature	From -10 to +60 C
Operating temperature	From 0 to +50 C
GENERAL INFORMATION	
Housing material	Stainless steel
Dimensions of the terminal	800x600x300 mm
Number of cable glands	From 1 to 12
Cable glands material	Nickel-plated brass or polyamide
ACCESSORIES	
Industrial printer	Option
Barcode reader	Option
IP intercom	Option
Thermoelectric cooling (Peltier device)	Option
Heating	100W heater (with blower)
Cooling	Using a fan
Industrial computer	Yes

ORDERING INFORMATION	
PRODUCT	ORDERING KEY
STX 5000T	HDW-STX-5000T

* The manufacturer reserves itself the right to amend product features. Product parameters may be amended without any prior notice.
 GS Software Sp. z o.o., ul. Ogłęczyna 20, 31-589 Kraków, Poland. More to be found at www.gs-software.co.uk